

# Broadway

- A versatile design based around a cast aluminium chassis. A variety of mounting options. Sealed optical compartment for ease of maintenance and vandal resistant. Available in 500, 600 and 700mm diameters.
- Various optics/reflector options to reduce light pollution and skyglow, while providing a variety of distributions appropriate to most applications
- Ease of maintenance with no-tool access and 1/4 turn sealed lamp holder design
- Top entry version can use EasyFit adapter for ease of installation and accurate alignment of luminaire. Side entry and Stirrup mounting also available
- IP66 optical compartment




## Technical info

Materials	Body: Cast aluminium LM6 chassis with spun aluminium canopy Glazing: Double UV stable polycarbonate, Acrylic optional
Ingress Protection	IP66 optical compartment IP44 gear compartment
Finishes	Polyester powdercoat to any BS / RAL colours Stoving acrylic painted to any BS / RAL colours
Optics	Can accommodate our full range of optics for both street and car park lighting
Gear	Upto 250W SONT Upto 250W MH Upto 140W Cosmopolis Upto 250W Ceramic Metal Halide LED Array Compact Fluorescent
Fixings	Stainless Steel
Recommended Height	6m -12m
Mounting	Top entry Side mount Post top via stirrup bracket
Mounting Details	Suspended via Candela Easy Fit adaptor Side entry via dia 42mm spigot Post top bracket to suit a wide range of column and spigot sizes
Maintenance	Drop down plate hinges for access to gear and lamp. Lamp change via 1/4 turn lampholder. No tools required
Weight	17kg's dependant on gear Call for specific details
Photo Cell	Miniature PEC

## Typical Applications

- ✓ Carpark
- ✓ Street/Highway
- ✓ Amenity
- ✓ Exterior



c a n d e l a

L I G H T