

Neos

- The Neos embodies style, elegance and practical solution. The EV2 optic offers class - leading performance for a wide range of applications
- Contemporary solution to street and amenity lighting
- Fully die-cast aluminium construction for robustness and cool operation
- Universal mount for 76mm post top or 34/42mm side entry
- Two sizes available
- Various optics / reflector options to reduce light pollution and skyglow, while providing a variety of distributions appropriate to most applications
- Ease of maintenance with no-tool access and 1/4 turn sealed lamp holder design





Technical info

Materials	Body: Die cast aluminium Glazing: Double UV stable polycarbonate, Acrylic optional
Ingress Protection	IP66 optical compartment IP44 gear compartment
Finishes	Polyester powdercoat to any BS / RAL colours Stoving acrylic painted to any BS / RAL colours
Optics	Can accommodate our range of optics for both street and car park lighting Call for details
Gear	Upto 250W SONT Upto 250W MH Upto 140W Cosmopolis Upto 250W Ceramic Metal Halide LED Array Compact Fluorescent
Fixings	Stainless Steel
Recommended Height	6 m - 10 m
Mounting	Post-top Side entry
Mounting Details	Post top dia 76mm spigot Side entry dia 42mm spigot no adaptors required
Maintenance	Drop down plate hinges for access to gear and lamp. Lamp change via 1/4 turn lampholder. No tools required
Weight	17kg's dependant on gear Call for specific details
Photo Cell	Miniature PEC Nema socket

Typical Applications

- ✔ Carpark
- ✔ Amenity
- ✔ Street/Highway
- ✔ Exterior
- ✔ House Builder



candela

L I G H T